

# Combination Hammer

## HR2600

800 W • SDS-Plus • 26 mm • 2,9 J

### Professional two-mode rotary hammer

Efficient combination hammer compatible with SDS-Plus bits. Suitable for impact and unstressed drilling. Motor capacity of 800 W and speed can be adjusted between 0 and 1 200 min<sup>-1</sup> from a switch. Impact energy of 2,9 J and optimal drilling range of 8 – 18 mm in concrete. Max. drilling capacity of 26 mm in concrete.



### TECHNICAL SPECIFICATIONS

Maximum Output Power	800 W
No load speed	0 - 1200 min <sup>-1</sup>
Impact	0 - 4600 min <sup>-1</sup>
Max. Drilling Diameter in Wood	32 mm
Max. Drilling Diameter in Concrete	26 mm
Max. Drilling Diameter in Steel	13 mm
Optimum Drilling Diameter Range in Concrete	8 - 18 mm
Impact Energy	2,4 J
Drilling diameter with TCT core bit	68 mm
Power Supply Cord	2,5 m
Side Grip	✓
Depth Gauge (2)	✓
Sound Power Level (L <sub>WA</sub> )	102 dB(A)
Sound Pressure Level (L <sub>pA</sub> )	91 dB(A)

### USER BENEFITS

- 2-mode operation for "Rotation Only" or "Hammering with Rotation"
- 360° swivel side handle
- Variable speed
- Ergonomic handle
- Double insulated

[Link to Product page - www.makita.ae](http://www.makita.ae)



# RELATED PRODUCTS

## ■ OTHER

User manual

