

# HIOKI

## WIRELESS ADAPTER Z3210

**NEW**

**Easy to set up!  
Simply plug in the Z3210 wireless adapter and  
your compatible HIOKI device is Bluetooth®  
ready!**



### Get connected!

Work even smarter with our new Z3210 wireless adapter!  
Now you can create and share graphical reports in a flash!

Z3210 is a Bluetooth® wireless adapter that will:

- Increase your work efficiency, by eliminating human errors from manual reporting
- Transfer readings on instruments to easy-to-read graphical reports to prove integrity
- Increase your work productivity & save costs!
- Provide additional new functions for HIOKI devices such as waveform display & more!



Easy set up



Item	Value	Unit	Alarm
Temperature	14.34	°C	OK
Humidity	60.01	%	OK

GENNECT Cross App

Excel® Direct Input



## Specifications

Operating environment	Indoors, pollution degree 2, operable at an altitude specified in specifications of each measuring instrument to which the adapter is attached
Operating temperature and humidity (Storage temperature and humidity)	-30°C (-22°F) to 70°C (158°F) 90% RH or less (no condensation)
Standards	Safety: EN61010, RF: EN300 328, RF EMC: EN301 489-1, EN301 489-17, Exposure: EN62479
Maximum attaching/detaching count	5,000 times (Can be switched between compatible measuring instruments)

## Model



**Model: WIRELESS ADAPTER Z3210**  
**Model No. (Order code): Z3210**



**Z3210 web site**  
 For more information on supported regions and products, please visit this dedicated site.

GENNECT Cross App Confirmed compatible OSs	iOS 13 or later, Android 9 or later, Bluetooth® 4.0 or later
Excel® Direct Input Confirmed compatible OSs	Windows 10, iOS 13 or later, Android 9 or later, Bluetooth® 4.0 or later
Bluetooth® Communication distance	About 10 m (line-of-sight distance)
Product warranty period	3 years (except for the connector. Depending on your tablet/smartphone, you may not be able to connect)
Dimensions and Mass	Approx. 16.4 mmW x 6.7 mmH x 15.6 mmD (0.65" W x 0.26" H x 0.61" D), Approx. 1.5 g (0.05 oz.)
Accessory	Instruction manual

## Compatible products (scheduled included)

<b>AC LEAKAGE CLAMP METER</b> CM4001, CM4002, CM4003	<b>AC CLAMP POWER METER</b> CM3286-50	<b>AC CLAMP METER</b> CM4141-50	<b>AC/DC CLAMP METER</b> CM4371-50 CM4373-50 CM4375-50	<b>DIGITAL MULTI METER</b> DT4261
<b>BATTERY TESTER</b> BT3554-50	<b>DIGITAL PHASE DETECTOR</b> PD3259-50	<b>INSULATION TESTER</b> IR4057-50	<b>EARTH TESTER</b> FT6031-50	<b>CLAMP ON EARTH TESTER</b> FT6380-50

**More compatible HIOKI products and apps are on their way**



### Downloading GENNECT Cross

GENNECT Cross is a free app. Download it to your tablet or smartphone from Google Play™ or App Store™. Simply search for "HIOKI" and download "GENNECT Cross" today!



\*The Bluetooth® word mark and logos are registered trademarks owned by Bluetooth SIG, Inc. and any use of such marks by HIOKI E. E. CORPORATION is under license. © 2022 HIOKI E. E. CORPORATION. All rights reserved.

DISTRIBUTED BY

**HIOKI**  
**HIOKI E. E. CORPORATION**

**HEADQUARTERS**  
 81 Kozurni,  
 Ueda, Nagano 386-1192 Japan  
<https://www.hioki.com/>



Scan for all regional contact information